







电气材料清单







#	名称	制造商	零件编号	属性	Qty	Price	大小
1.	Cboot	AVX	08053C104KAT2A Series= X7R	Cap= 100.0 nF ESR= 280.0 mOhm VDC= 25.0 V IRMS= 0.0 A	1	\$0.01	 0805 13mm2
2.	Cff	MuRata	GRM1555C1E5R1CA01D Series= C0G/NP0	Cap= 5.1 pF VDC= 25.0 V IRMS= 0.0 A	1	\$0.01	 0402 8mm2
3.	Cin	MuRata	GRM32ER61E226KE15L Series= X5R	Cap= 22.0 uF ESR= 2.0 mOhm VDC= 25.0 V IRMS= 3.67 A	1	\$0.31	 1210 23mm2
4.	Cout	MuRata	GRM31CR60J476ME19L Series= X5R	Cap= 47.0 uF ESR= 3.0 mOhm VDC= 6.3 V IRMS= 0.0 A	1	\$0.20	 1206 19mm2
5.	Creg	MuRata	GRM155R61A105KE15D Series= X5R	Cap= 1.0 uF VDC= 10.0 V IRMS= 0.0 A	1	\$0.01	 0402 8mm2
6.	Css	MuRata	GRM155R71E822KA01D Series= X7R	Cap= 8.2 nF VDC= 25.0 V IRMS= 0.0 A	1	\$0.01	 0402 8mm2
7.	L1	Bourns	SRN3015-2R2M	L= 2.2 uH DCR= 72.0 mOhm	1	\$0.13	 SRN3015 25mm2
8.	Ren	Vishay-Dale	CRCW040210K0FKED Series= CRCW..e3	Res= 10.0 kOhm Power= 63.0 mW Tolerance= 1.0%	1	\$0.01	 0402 8mm2
9.	Rfbb	Vishay-Dale	CRCW040222K1FKED Series= CRCW..e3	Res= 22.1 kOhm Power= 63.0 mW Tolerance= 1.0%	1	\$0.01	 0402 8mm2
10.	Rfbb	Vishay-Dale	CRCW040275K0FKED Series= CRCW..e3	Res= 75.0 kOhm Power= 63.0 mW Tolerance= 1.0%	1	\$0.01	 0402 8mm2





#	名称	制造商	零件编号	属性	Qty	Price	大小
11.	U1	Texas Instruments	TPS54427DDAR	Switcher	1	\$1.63	



R-PDSO-G8 57mm2







工作数值

#	名称	数值	类别	说明
1.	Cin IRMS	392.728 mA	Current	输入电容器均方根纹波电流
2.	Cout IRMS	516.562 mA	Current	输出电容器均方根纹波电流
3.	IC Ipk	1.895 A	Current	电路内的峰值开关电流
4.	Iin Avg	207.36 mA	Current	平均输入电流
5.	L Ipp	1.789 A	Current	峰值到峰值电感器纹波电流
6.	BOM 数量	11	General	Total Design BOM count
7.	大小	183.0 mm ²	General	BOM组件的总所占面积
8.	频率	711.494 kHz	General	开关频率
9.	模式	CCM	General	传导模式
10.	Pout	3.3 W	General	总输出功率
11.	总 BOM	\$2.34	General	Total BOM Cost
12.	Vout OP	3.3 V	Op_Point	Operational Output Voltage
13.	占空比	19.054 %	Op_point	占空比
14.	效率	88.414 %	Op_point	稳态效率
15.	IC Tj	45.463 degC	Op_point	电路接点温度
16.	IC ThetaJA	45.3 degC/W	Op_point	电路接点到环境热敏电阻
17.	IOUT_OP	1.0 A	Op_point	Iout 操作点
18.	VIN_OP	18.0 V	Op_point	Vin操作点
19.	Vout p-p	10.694 mV	Op_point	峰值到峰值输出纹波电压
20.	Cin Pd	308.471 μW	Power	输入电容器功率耗散
21.	Cout Pd	800.508 μW	Power	输出电容器功率耗散
22.	电路静态电流功率耗散	16.56 mW	Power	电路静态电流功率耗散
23.	IC Pd	341.351 mW	Power	电路功率耗散
24.	L Pd	90.0 mW	Power	电感器功率耗散
25.	整体 Pd	432.445 mW	Power	总功率耗散

设计输入

#	名称	数值	说明
1.	输出电流	1.0 A	最大输出电流
2.	Iout1	1.0 Amps	Output Current #1

#	名称	数值	说明
3.	Vin 最大	18.0 V	最高输入电压
4.	Vin 最小	14.0 V	最低输入电压
5.	输出电压:	3.3 V	输出电压
6.	Vout1	3.3 Volt	Output Voltage #1
7.	base_pn	TPS54427	美国国家半导体的产品编号
8.	源	DC	输入源类别
9.	工作环境温度	30.0 degC	环境温度

设计协助

1. TPS54427 Product Folder : <http://www.ti.com/product/tps54427> : contains the data sheet and other resources.

Texas Instruments' WEBENCH simulation tools attempt to recreate the performance of a substantially equivalent physical implementation of the design. Simulations are created using Texas Instruments' published specifications as well as the published specifications of other device manufacturers. While Texas Instruments does update this information periodically, this information may not be current at the time the simulation is built. Texas Instruments does not warrant the accuracy or completeness of the specifications or any information contained therein. Texas Instruments does not warrant that any designs or recommended parts will meet the specifications you entered, will be suitable for your application or fit for any particular purpose, or will operate as shown in the simulation in a physical implementation. Texas Instruments does not warrant that the designs are production worthy.

You should completely validate and test your design implementation to confirm the system functionality for your application prior to production.

Use of Texas Instruments' WEBENCH simulation tools is subject to [Texas Instruments' Site Terms and Conditions of Use](#). Prototype boards based on WEBENCH created designs are provided AS IS without warranty of any kind for evaluation and testing purposes and are subject to the terms of the [Evaluation License Agreement](#).