WEBENCH ® Design Report

VinMin = 22.0V
VinMax = 26.0V
Vout = 5.0V
Iout = 5.0A

Device = LM25085MY/NOPB
Topology = Buck
Created = 4/14/16 6:57:07 PM
BOM Cost = $2.92
BOM Count = 14
Total Pd = 4.17W

Design : 4529086/19 LM25085MY/NOPB
LM25085MY/NOPB 22.0V-26.0V to 5.00V @ 5.0A



Electrical BOM

#	Name	Manufacturer	Part Number	Properties	Qty	Price	Footprint
1.	Cadj	Samsung Electro-Mechanics	CL21C102JBCNFNC Series= C0G/NP0	Cap= 1.0 nF VDC= 50.0 V IRMS= 0.0 A	1	$0.01	0805 7 mm²
2.	Cff	Kemet	C0805C821K5RACTU Series= X7R	Cap= 820.0 pF ESR= 425.0 mOhm VDC= 50.0 V IRMS= 204.0 mA	1	$0.05	0805 7 mm²
3.	Cin	MuRata	GRM31CR71H475KA12L Series= X7R	Cap= 4.7 uF ESR= 3.0 mOhm VDC= 50.0 V IRMS= 4.98 A	1	$0.07	1206 11 mm²
4.	Cout	Panasonic	6TPU47MSI Series= TPU	Cap= 47.0 uF ESR= 150.0 mOhm VDC= 6.3 V IRMS= 510.0 mA	1	$0.46	CAPSMT_6_S09 7 mm²
5.	Cvcc	AVX	0805YC474KAT2A Series= X7R	Cap= 470.0 nF ESR= 11.0 mOhm VDC= 16.0 V IRMS= 0.0 A	1	$0.02	0805 7 mm²
6.	D1	Vishay-Semiconductor	50WQ04FNPBF	VF@Io= 510.0 mV VRRM= 40.0 V	1	$0.40	DPAK 102 mm²
7.	L1	Coilcraft	XAL6060-822MEB	L= 8.2 µH DCR= 24.0 mOhm	1	$0.82	XAL6060 72 mm²
8.	M1	Fairchild Semiconductor	FDD5614P	VdsMax= -60.0 V IdsMax= -15.0 Amps	1	$0.24	DPAK 102 mm²
9.	Radj	Vishay-Dale	CRCW04022K21FKED Series= CRCW..e3	Res= 2.21 kOhm Power= 63.0 mW Tolerance= 1.0%	1	$0.01	0402 3 mm²

Copyright © 2016, Texas Instruments Incorporated

#	Name	Manufacturer	Part Number	Properties	Qty	Price	Footprint
10.	Rfb1	Vishay-Dale	CRCW04023K32FKED Series= CRCW..e3	Res= 3.32 kOhm Power= 63.0 mW Tolerance= 1.0%	1	$0.01	0402 3 mm²
11.	Rfb2	Vishay-Dale	CRCW040210K0FKED Series= CRCW..e3	Res= 10.0 kOhm Power= 63.0 mW Tolerance= 1.0%	1	$0.01	0402 3 mm²
12.	Rsns	Stackpole Electronics Inc	CSR1206FK10L0 Series= ?	Res= 10.0 mOhm Power= 500.0 mW Tolerance= 1.0%	1	$0.11	1206 11 mm²
13.	Rt	Vishay-Dale	CRCW040278K7FKED Series= CRCW..e3	Res= 78.7 kOhm Power= 63.0 mW Tolerance= 1.0%	1	$0.01	0402 3 mm²
14.	U1	Texas Instruments	LM25085MY/NOPB	Switcher	1	$0.70	MUY08A 24 mm²









Copyright © 2016, Texas Instruments Incorporated













Copyright © 2016, Texas Instruments Incorporated













Copyright © 2016, Texas Instruments Incorporated













Copyright © 2016, Texas Instruments Incorporated



Operating Values

#	Name	Value	Category	Description
1.	Cin IRMS	2.034 A	Current	Input capacitor RMS ripple current
2.	Cout IRMS	387.937 mA	Current	Output capacitor RMS ripple current
3.	Iin Avg	1.122 A	Current	Average input current
4.	L Ipp	1.344 A	Current	Peak-to-peak inductor ripple current
5.	SW Ipk	5.672 A	Current	Peak switch current
6.	BOM Count	14	General	Total Design BOM count
7.	FootPrint	359.0 mm^2	General	Total Foot Print Area of BOM components
8.	Frequency	334.598 kHz	General	Switching frequency
9.	IC Tolerance	25.0 mV	General	IC Feedback Tolerance
10.	Pout	25.0 W	General	Total output power
11.	Total BOM	$2.92	General	Total BOM Cost
12.	D1 Tj	104.398 degC	Op_Point	D1 junction temperature
13.	Vout Actual	5.015 V	Op_Point	Vout Actual calculated based on selected voltage divider resistors
14.	Vout OP	5.0 V	Op_Point	Operational Output Voltage
15.	Duty Cycle	20.931 %	Op_point	Duty cycle
16.	Efficiency	85.717 %	Op_point	Steady state efficiency
17.	IC Tj	38.698 degC	Op_point	IC junction temperature
18.	ICThetaJA	46.0 degC/W	Op_point	IC junction-to-ambient thermal resistance
19.	IOUT_OP	5.0 A	Op_point	Iout operating point
20.	M1 Tj	70.633 degC	Op_point	M1 MOSFET junction temperature
21.	VIN_OP	26.0 V	Op_point	Vin operating point
22.	Vout p-p	201.861 mV	Op_point	Peak-to-peak output ripple voltage
23.	Cin Pd	12.412 mW	Power	Input capacitor power dissipation
24.	Cout Pd	22.574 mW	Power	Output capacitor power dissipation
25.	Diode Pd	1.653 W	Power	Diode power dissipation
26.	IC Pd	189.092 mW	Power	IC power dissipation
27.	L Pd	750.0 mW	Power	Inductor power dissipation
28.	M1 Pd	1.288 W	Power	M1 MOSFET total power dissipation
29.	M1 PdCond	1.222 W	Power	M1 MOSFET conduction losses
30.	M1 PdSw	66.555 mW	Power	M1 MOSFET switching losses
31.	Total Pd	4.166 W	Power	Total Power Dissipation
32.	Vout Tolerance	1.92 %		Vout Tolerance based on IC Tolerance and voltage divider resistors if applicable

Design Inputs

#	Name	Value	Description
1.	Iout	5.0	Maximum Output Current
2.	VinMax	26.0	Maximum input voltage
3.	VinMin	22.0	Minimum input voltage
4.	Vout	5.0	Output Voltage
5.	base_pn	LM25085	Texas Instruments Base Part Number
6.	source	DC	Input Source Type
7.	ta	30.0	Ambient temperature

Design Assistance

1. For a Constant On Time device to be stable, we need to provide a ripple at the feedback comparator. There are various methods to implement the ripple. Depending on the circuit complexity vs. the allowable ripple, we have three options to choose from. The simplest option, 'Low Complexity', would require only a high ESR cap at the output. This means that the BOM count will be small, but the output voltage ripple will be quite large. The 'optimal solution' would require a feed-forward cap in parallel with the upper feedback resistor to AC couple the ripple to

Copyright © 2016, Texas Instruments Incorporated

the feedback node. This increases the BOM count slightly, but now we have more control over the output voltage ripple. If the output voltage requirement is very tight, then the best option is to go for the 'Low Output Ripple' solution. In this option we can go with very low ESR output caps and have very good control over the output voltage ripple

2. LM25085 Product Folder : http://www.ti.com/product/LM25085 : contains the data sheet and other resources.

Texas Instruments' WEBENCH simulation tools attempt to recreate the performance of a substantially equivalent physical implementation of the design. Simulations are created using Texas Instruments' published specifications as well as the published specifications of other device manufacturers. While Texas Instruments does update this information periodically, this information may not be current at the time the simulation is built. Texas Instruments does not warrant the accuracy or completeness of the specifications or any information contained therein. Texas Instruments does not warrant that any designs or recommended parts will meet the specifications you entered, will be suitable for your application or fit for any particular purpose, or will operate as shown in the simulation in a physical implementation. Texas Instruments does not warrant that the designs are production worthy.

You should completely validate and test your design implementation to confirm the system functionality for your application prior to production.

Use of Texas Instruments' WEBENCH simulation tools is subject to Texas Instruments' Site Terms and Conditions of Use. Prototype boards based on WEBENCH created designs are provided AS IS without warranty of any kind for evaluation and testing purposes and are subject to the terms of the Evaluation License Agreement.