



ISO/IEC JTC 1/SC 17  
Cards and personal identification  
Secretariat: BSI

**Document type:** Text for PDAM ballot or comment

**Title:** ISO/IEC 14443-2:2010/PDAM 4.2 - Identification cards - Contactless integrated circuit cards - Proximity cards - Part 2: Radio frequency power and signal interface

**Status:**

**BACKWARD POINTER:** N 3680, N 3744, N 3834, N 3901 and N 3958

**STATUS:** This ballot has been posted to the ISO Electronic balloting application and is available under the Balloting Portal, Committee Internal Balloting.

**WORK ITEM:** 54563

**Date of document:** 2010-06-23

**Expected action:** VOTE

**Action due date:** 2010-09-15

**Email of secretary:** [chris.starr@ukpayments.org.uk](mailto:chris.starr@ukpayments.org.uk)

**Committee URL:** <http://isotc.iso.org/livelink/livelink/open/jtc1sc17>

ISO/IEC JTC 1/SC 17 N

Date: 2010-04-30

ISO/IEC 14443-2:2010/PDAM 4.2

ISO/IEC JTC 1/SC 17/WG 8

Secretariat: DIN

## Identification cards — Contactless integrated circuit cards — Proximity cards — Part 2: Radio frequency power and signal interface

### AMENDMENT 4

#### Additional PICC classes

*Cartes d'identification — Cartes à circuit(s) intégré(s) sans contact — Cartes de proximité — Partie 2: Interface radio fréquence*

### AMENDEMENT 4

#### Classes de PICC additionnelles

#### Warning

This document is not an ISO International Standard. It is distributed for review and comment. It is subject to change without notice and may not be referred to as an International Standard.

Recipients of this draft are invited to submit, with their comments, notification of any relevant patent rights of which they are aware and to provide supporting documentation.

Document type: International Standard

Document subtype: Amendment

Document stage: (30) Committee

Document language: E

### Copyright notice

This ISO document is a working draft or committee draft and is copyright-protected by ISO. While the reproduction of working drafts or committee drafts in any form for use by participants in the ISO standards development process is permitted without prior permission from ISO, neither this document nor any extract from it may be reproduced, stored or transmitted in any form for any other purpose without prior written permission from ISO.

Requests for permission to reproduce this document for the purpose of selling it should be addressed as shown below or to ISO's member body in the country of the requester:

[Indicate the full address, telephone number, fax number, telex number, and electronic mail address, as appropriate, of the Copyright Manager of the ISO member body responsible for the secretariat of the TC or SC within the framework of which the working document has been prepared.]

Reproduction for sales purposes may be subject to royalty payments or a licensing agreement.

Violators may be prosecuted.

## Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

Amendment 4 to ISO/IEC 14443-2:2010 was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 17, *Cards and personal identification*.



## Identification cards — Contactless integrated circuit cards — Proximity cards — Part 2: Radio frequency power and signal interface

### AMENDMENT 4: Additional PICC classes

*Page 3 of ISO/IEC 14443-2:2010, Clause 4*

Add the following symbol definitions:

$V_{LMA, PCD}$	Maximum load modulation amplitude for PCD reception
$V_{LMA, PICC}$	Minimum load modulation amplitude for PICC transmission

*Page 4 of ISO/IEC 14443-2:2010, Clause 6*

Replace 6.2 by the following subclause:

#### **6.2 Operating field**

The PCD shall generate a field strength of at least  $H_{min}$  and not exceeding  $H_{max}$  at manufacturer specified positions (operating volume) under unmodulated conditions.

The PCD

- shall support PICCs of "Class 1", "Class 2" and "Class 3";
- may optionally support PICCs of "Class 4";
- may optionally support PICCs of "Class 5";
- and may optionally support PICCs of "Class 6".

PCD requirements measured with Reference PICCs 1, 2 and 3 are mandatory for all PCDs.

PCD requirements measured with Reference PICC 4 are only mandatory for PCDs supporting operation with "Class 4" PICCs.

PCD requirements measured with Reference PICC 5 are only mandatory for PCDs supporting operation with "Class 5" PICCs.

PCD requirements measured with Reference PICC 6 are only mandatory for PCDs supporting operation with "Class 6" PICCs.

Table 1 — PCD field strength

	PCD	
	$H_{\min}$	$H_{\max}$
Measured with Reference PICC 1	1,5 A/m (rms)	7,5 A/m (rms)
Measured with Reference PICC 2	1,5 A/m (rms)	8,5 A/m (rms)
Measured with Reference PICC 3	1,5 A/m (rms)	8,5 A/m (rms)
Measured with Reference PICC 4 (optional)	2,0 A/m (rms)	12 A/m (rms)
Measured with Reference PICC 5 (optional)	2,5 A/m (rms)	14 A/m (rms)
Measured with Reference PICC 6 (optional)	4,5 A/m (rms)	18 A/m (rms)

The PCD shall not generate a field strength higher than the value specified in ISO/IEC 14443-1:2008, 4.4 (alternating magnetic field) in any possible PICC position and orientation, measured with Reference PICC 1.

Test methods for the PCD operating field are defined in ISO/IEC 10373-6 and use a dedicated Reference PICC for each class.

NOTE 1 Although field measurements with some Reference PICCs may show values higher than 7,5 A/m (rms), the new  $H_{\max}$  limits specified in Table 1 do not allow PCDs to produce higher field strength than with first edition of ISO/IEC 14443-2. This is because PCD field distribution is usually not homogenous within the operating volume and References PICCs have different measurement areas.

If the PICC meets the requirements of one particular class as specified in ISO/IEC 14443-1:2008/AMD1, then the PICC shall operate as intended continuously between  $H_{\min}$  and  $H_{\max}$  defined for its class; this includes all PICC requirements defined in this standard and processing of the manufacturer specified set of commands.

If the PICC does not claim to meet the requirements of one particular class as specified in ISO/IEC 14443-1:2008/AMD1, then:

- if the PICC antenna fits within the external rectangle defined in "Class 2" as specified in ISO/IEC 14443-1:2008/AMD1, the electrical requirements and test methods for "Class 1" or "Class 2" shall apply;
- if the PICC antenna fits within the external rectangle or external circle defined in "Class 3" as specified in ISO/IEC 14443-1:2008/AMD1, the electrical requirements and test methods for "Class 1" or "Class 3" shall apply;
- if the PICC antenna does not claim to fit within the external rectangle or external circle defined in "Class 2" or "Class 3" as specified in ISO/IEC 14443-1:2008/AMD1, the electrical requirements and test methods for "Class 1" shall apply.

**Table 2 — PICC operating field strength**

	PICC	
	$H_{\min}$	$H_{\max}$
"Class 1" PICC	1,5 A/m (rms)	7,5 A/m (rms)
"Class 2" PICC	1,5 A/m (rms)	8,5 A/m (rms)
"Class 3" PICC	1,5 A/m (rms)	8,5 A/m (rms)
"Class 4" PICC	2,0 A/m (rms)	12 A/m (rms)
"Class 5" PICC	2,5 A/m (rms)	14 A/m (rms)
"Class 6" PICC	4,5 A/m (rms)	18 A/m (rms)

NOTE 2 Margins are effectively included by the test methods as specified in ISO/IEC 10373-6.

Page 15 of ISO/IEC 14443-2:2010, 8.2

Replace 8.2.2 by the following subclause and renumber all subsequent tables:

### 8.2.2 Load modulation

The PICC shall be capable of communication to the PCD via an inductive coupling area where the carrier frequency is loaded to generate a subcarrier with frequency  $f_s$ . The subcarrier shall be generated by switching a load in the PICC.

If the PICC meets the requirements of one particular class as specified in ISO/IEC 14443-1:2008/AMD1, then the load modulation amplitude  $V_{LMA}$  of the PICC shall be at least  $V_{LMA, PICC}$  specified for its class when measured as described in ISO/IEC 10373-6, using the test PCD assembly defined for its class, where  $H$  is the (rms) value of magnetic field strength in A/m.

If the PICC does not claim to meet the requirements of one particular class as specified in ISO/IEC 14443-1:2008/AMD1, then the load modulation amplitude  $V_{LMA}$  of the PICC shall be at least  $V_{LMA, PICC}$  specified for "Class 1" when measured as described in ISO/IEC 10373-6, using the test PCD assembly defined for "Class 1", where  $H$  is the (rms) value of magnetic field strength in A/m.

Table 8 specifies for each PICC class both the load modulation amplitude limit  $V_{LMA, PICC}$  and the relevant test PCD assembly to measure the PICC load modulation amplitude  $V_{LMA}$ .

**Table 8 — PICC load modulation amplitude limit**

	PICC	
	$V_{LMA, PICC}$	Test PCD assembly
"Class 1" PICC	$22/H^{0.5}$ [mV (peak)]	Test PCD assembly 1
"Class 2" PICC	$22/H^{0.5}$ [mV (peak)]	Test PCD assembly 1
"Class 3" PICC	$\text{Min}(9 ; 22/H^{0.5})$ [mV (peak)]	Test PCD assembly 1
"Class 4" PICC	$\text{Min}(18 ; 44/H^{0.5})$ [mV (peak)]	Test PCD assembly 2
"Class 5" PICC	$\text{Min}(18 ; 44/H^{0.5})$ [mV (peak)]	Test PCD assembly 2
"Class 6" PICC	8 mV (peak)]	Test PCD assembly 2



The PCD shall be able to receive a  $V_{LMA}$  of at least  $V_{LMA, PCD}$  when measured as described in ISO/IEC 10373-6, using test PCD assembly 1, with Reference PICCs 1, 2 and 3, where  $H$  is the (rms) value of magnetic field strength in A/m.

If the PCD supports operation with "Class 4" PICCs, it shall be able to receive a  $V_{LMA}$  of at least  $V_{LMA, PCD}$  when measured as described in ISO/IEC 10373-6, using test PCD assembly 2, with Reference PICC 4, where  $H$  is the (rms) value of magnetic field strength in A/m.

If the PCD supports operation with "Class 5" PICCs, it shall be able to receive a  $V_{LMA}$  of at least  $V_{LMA, PCD}$  when measured as described in ISO/IEC 10373-6, using test PCD assembly 2, with Reference PICC 5, where  $H$  is the (rms) value of magnetic field strength in A/m.


If the PCD supports operation with "Class 6" PICCs, it shall be able to receive a  $V_{LMA}$  of at least  $V_{LMA, PCD}$  when measured as described in ISO/IEC 10373-6, using test PCD assembly 2, with Reference PICC 6, where  $H$  is the (rms) value of magnetic field strength in A/m.

Table 9 specifies for each Reference PICC both the load modulation reception limit  $V_{LMA, PCD}$  and the test PCD assembly to use to measure the PCD sensitivity.

**Table 9 — PCD load modulation reception limit**

	PCD	
	$V_{LMA, PICC}$	Test PCD assembly
Measured with Reference PICC 1	$18/H^{0.5}$ [mV (peak)]	Test PCD assembly 1
Measured with Reference PICC 2	$18/H^{0.5}$ [mV (peak)]	Test PCD assembly 1
Measured with Reference PICC 3	$\text{Min}(8 ; 18/H^{0.5})$ [mV (peak)]	Test PCD assembly 1
Measured with Reference PICC 4 (optional)	$\text{Min}(16 ; 36/H^{0.5})$ [mV (peak)]	Test PCD assembly 2
Measured with Reference PICC 5 (optional)	$\text{Min}(16 ; 36/H^{0.5})$ [mV (peak)]	Test PCD assembly 2
Measured with Reference PICC 6 (optional)	7 mV (peak)]	Test PCD assembly 2

Figure 11 is an illustration of the PCD and PICC load modulation amplitude limits for each class.



**Figure 11 — Load modulation amplitude**

Editor's note: Figure 11 to be updated in FPDAM ballot with the PCD and PICC limits for each class

NOTE The PICC load modulation amplitude limits of classes 3 to 6 are less strict than the previous PICC limit in ISO/IEC 14443-2:2010.